

8 INCH WIDE KE081

8" Open Frame LCD Monitor



Model No : KE081

KE081T / touch panel

- Multi-input signal support
- LED backlight for power saving and environmental protection
- 4-wired resistive touch panel screen - available with KE081T
- Integrated bracket for easy installation
- Versatile mounting methods for rear mounting and VESA mounting



Features

KE081 is a cost-effective, high-quality open frame LCD monitor suitable for integration with any industrial or commercial application. KE081 features 800x600 resolution with wide view angles of 120(V)/140(H) degree and LED backlight TFT LCD panel, which saves more energy and lasts significantly longer than conventional CCFL backlights.

KE081 allows users to choose video input signals from HDMI, VGA and Video which deliver various display solutions for OEM's and integrators to easily integrate with various applications. 4-wired resistive touch panel model is also available for interactivity application.

■ Multi-input signal support

KE081 supports both digital and analog input signals with abundant input interfaces, HDMI, VGA and Video.



■ Control keys and a remote controller

Control keys are located at the back of the housing. On-Screen Display (OSD) menu is activated or selected through the control keys or a remote controller.



■ 4-wired resistive touch panel screen

KE081 is also available in 4-wired resistive touch panel screen with USB control interface, model KE081T. The touch panel screen model delivers interactive applications for control system, kiosk, digital signage, etc.

■ Rugged metal housing

KE081 is designed with open-frame typed and rugged metal housing. The monitor can be easily mounted into the cabinet through front open face mounting bracket or VESA mount.

■ Power saving model with LED backlightened LCD panel

LED backlightened TFT LCD panel saves more energy and lasts significantly longer than conventional CCFL backlights.

Specifications

Model	KE081
Panel Size	8"
Resolution	800*480
touch panel	4-wire resistive, USB(option)
Backlight	LED
Brightness	250
Contrast Ratio	500:1
View Angle	140° / 120° (H/V)
Input	HDMI, VGA, Video (RCA) x2
VESA (FPMPI)	○ (75×75mm)
Support Signal	NTSC/ PAL/ SECAM
Power	DC12V 1.2A
DPMS	Yes
Power Consumption	8W or less (operation)
Operating Temperature	0 to 40 degree
Storage Temperature	-20 to 60 degree
Dimension	220mm(W) x 137mm(H) x 42mm(D)
Weight	1100g
Package Contents	VGA cable / AC Adaptor / Remote Controller / Touch pen (*1) / Driver CD (*1)
Certification	FCC/ CE/ RoHS

*Specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here. Not responsible for typographical errors.
(*1) Only as for the touch panel model

Industrial LCD Monitors

Open Frame LCD Monitors

Option Accessories