

# 10.1 INCH WIDE KE101

10.1" Open Frame LCD Monitor



Model No : KE101  
KE101T / touch panel

- Multi-input signal support
- LED backlight for power saving and environmental protection
- 4-wired resistive touch panel screen - available with KE101T
- Integrated bracket for easy installation
- Versatile mounting methods for rear mounting and VESA mounting



## Features

KE101 is a cost-effective, high-quality open frame LCD monitor suitable for integration with any industrial or commercial application. KE101 features 800x600 resolution with wide view angles of 120(V)/140(H) degree and LED backlight TFT LCD panel, which saves more energy and lasts significantly longer than conventional CCFL backlights.

KE101 allows users to choose video input signals from HDMI, VGA and Video which deliver various display solutions for OEM's and integrators to easily integrate with various applications. 4-wired resistive touch panel model is also available for interactivity application.

### ■ Multi-input signal support

KE101 supports both digital and analog input signals with abundant input interfaces, HDMI, VGA and Video.



### ■ Control keys and a remote controller

Control keys are located at the back of the housing. On-Screen Display (OSD) menu is activated or selected through the control keys or a remote controller.



### ■ 4-wired resistive touch panel screen

KE101 is also available in 4-wired resistive touch panel screen with USB control interface, model KE101T. The touch panel screen model delivers interactive applications for control system, kiosk, digital signage, etc.

### ■ Rugged metal housing

KE101 is designed with open-frame type and rugged metal housing. The monitor can be easily mounted into the cabinet through front open face mounting bracket or VESA mount.

### ■ Power saving model with LED backlight LCD panel

LED backlight TFT LCD panel saves more energy and lasts significantly longer than conventional CCFL backlights.

## Specifications

Model	KE101
Panel Size	10.1"
Resolution	1024*600
touch panel	4-wire resistive,USB(option)
Backlight	LED
Brightness	200
Contrast Ratio	500:1
View Angle	140° /90° (H/V)
Input	HDMI , VGA, Video (RCA) x 2
VESA (FPMPMI)	○(75×75mm)
Support Signal	NTSC/ PAL/ SECAM
Power	DC12V 1.2A
DPMS	Yes
Power Consumption	10W or less (operation)
Operating Temperature	0 to 40 degree
Storage Temperature	-20 to 60 degree
Dimension	258mm(W) x 146mm(H) x 31mm(D)
Weight	1100g
Package Contents	VGA cable /AC Adaptor / Remote Controller /Touch pen (*1)/Driver CD (*1)
Certification	FCC/ CE/ RoHS

\*Specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here. Not responsible for typographical errors.  
(\*1)Only as for the touch panel model